

MONOBLOCK HEAT PUMP

ZHHH-P1-006K-R290-R5-M

Performance data – heating (EN 14511)

① A7/W35	Power range (min-max) ¹	kW	1,93 - 6,03
	Partial load ¹	kW	6,03
	Power consumption ¹	kW	1,25
	COP ¹		4,81
② A7/W55	Maximum power ²	kW	5,51
	Power consumption ²	kW	1,77
	COP ²		3,12
③ A2/W35	Maximum power ³	kW	5,17
	Power consumption ³	kW	1,22
	COP ³		4,25
④ A-7/W35	Maximum power ⁴	kW	3,97
	Power consumption ⁴	kW	1,14
	COP ⁴		3,48

Performance data – cooling

⑤ A35/W18	Maximum power ⁵	kW	5,00
	Power consumption ⁵	kW	1,63
	EER ⁵		3
⑥ A35/W7	Maximum power ⁶	kW	4,35
	Power consumption ⁶	kW	1,44
	EER ⁶		3,03

Product data

Pump type		air / water
Refrigerant type		R290
Refrigerant amount	kg	1,30
Maximum working pressure	bar	31
Compressor type		twin rotary
Adjustment type		electronic

Heating

Minimum working pressure	bar	1,0
Maximum working pressure	bar	3,0
Rated flow	m ³ /h	1,17
External operating temperature range	°C	from -22 to +35
Feed water temperature	°C	from +20 to +65

Physical dimensions

Depth x width x height	mm	505 x 1155 x 935
Weight	kg	132
Water connections		G 5/4 "
Sound power level	dB	48
Air flow	m ³ /h	2500

Electrical data

Electrical connection	V/Ph/Hz	230 / 1~ / 50
Protection rating		IP24
Electric heater power (option with hydrobox / hydrotower)	kW	3 / 6 / 9
Fan power consumption	W	50
Number of fans		1

SCOP

W35 4,95 / W55 3,54

Energy efficiency class

Device with a regulator – feed temperature 35°C / 55°C



Heating temperature: water I/O temperature: Ambient temperature:	① 30°C / 35°C	② 40°C / 45°C	③ 50°C / 55°C	④ 30°C / 35°C	Cooling temperature: water I/O temperature: Ambient temperature:	⑤ 23°C / 18°C	⑥ 12°C / 7°C
		DB 7°C / WB 6°C		DB 2°C / WB 1°C		DB 35°C	