

PRODUCT CARD							
Product information in accordance with (in accordance with EU Regulation No. 813/2013)							
Model: ZHHS-01-10K-R290-V5-M							
Air-to-water heat pump: YES							
Brine-to-water heat pump: NO							
Low-temperature heat pump: NO							
Equipped with a supplementary heater: NO							
Heat pump combination heater: NO							
Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application							
Parameters shall be declared for average climate conditions.							
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output	P_{rated}	7	kW	Seasonal space heating energy efficiency	η_s	154	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T_j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T_j			
$T_j = -7\text{ °C}$	P_{dh}	5,9	kW	$T_j = -7\text{ °C}$	COPd or PERd	2,13	-
$T_j = +2\text{ °C}$	P_{dh}	3,9	kW	$T_j = +2\text{ °C}$	COPd or PERd	4,08	-
$T_j = +7\text{ °C}$	P_{dh}	2,8	kW	$T_j = +7\text{ °C}$	COPd or PERd	5,41	-
$T_j = +12\text{ °C}$	P_{dh}	3,2	kW	$T_j = +12\text{ °C}$	COPd or PERd	6,55	-
$T_j = \text{bivalent temperature}$	P_{dh}	6,6	kW	$T_j = \text{bivalent temperature}$	COPd or PERd	1,83	-
$T_j = \text{operation limit temperature}$	P_{dh}	6,6	kW	$T_j = \text{operation limit temperature}$	COPd or PERd	1,83	-
For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$)	P_{dh}	-	kW	For air-to-water heat pumps: $T_j = -15\text{ °C}$ (if $TOL < -20\text{ °C}$)	COPd or PERd	-	-
Bivalent temperature	T_{biv}	-10	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	P_{cyc}	-	kW	Cycling interval efficiency	COPcyc or PERcyc	-	-
Degradation co-efficient (**)	C_{dh}	0,97	-	Heating water operating limit temperature	WTOL	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	P_{OFF}	0,013	kW	Rated heat output	P_{sup}	0,040	kW
Thermostat-off mode	P_{TO}	0,013	kW	Type of energy input	Electric		
Standby mode	P_{SB}	0,013	kW				
Crankcase heater mode	P_{CK}	0,000	kW				
Other items							
Capacity control	Wydajność zmienna			Rated air flow rate, outdoors		3500	m ³ /h
Sound power level outdoors	L_{WA}	59	Rated brine or water flow rate, outdoor heat exchanger	Rated brine or water flow rate, outdoor heat exchanger		-	m ³ /h
Annual electricity consumption	Q_{HE}	3475/13	kWh/GJ				

Product information (in accordance with EU Regulation No. 811/2013)			
Supplier Name:		JBG-2 Sp. z o.o.	
Contact details:		ul. Gajowa 5, 43-254 Warszowice, Poland	
Supplier's model identifier:		ZHHS-01-10K-R290-V5-M	
Average climate	Seasonal space heating energy efficiency class	W35	A+++
		W55	A+++
	Seasonal space heating energy efficiency	W35	198%
		W55	154%
	Rated heat output	W35	7 kW
		W55	7 kW
	Annual electricity consumption	W35	2708 kWh/year
		W55	3475 kWh/year
SCOP	W35	5,04	
	W55	3,92	
Cold climate	Rated heat output	W35	9 kW
Warm climate		W55	9 kW
			W35
W55			7 kW
Outdoors	Sound power level L_{wa}	59dB	
Special precautions for assembly, installation and maintenance are included in the separate file named: „Precautions Heat Pump JBG2.pdf”			

W35- low temperature heating; W- water temperature at the outlet from the heat pump

W55- medium temperature heating; W- water temperature at the outlet from the heat pump